

Hydrocyclone Mud Cleaning System

Oil-based or water-based mud cleaner (2000 gal/min)



Specifications

- Double headers bolted over a Series 500B4X Linear Dryer.
- 2 - Vibrators, explosion proof, 3 phase, 230/460V, 60Hz, 1800 rpm.
- 3 - Panel, 25.3 sq.ft. screening area.
- API RP 13C Compliant Screens.
- Starter control, explosion proof, wired to both vibrators.
- Wedgelok System providing quick screen changes.
- 10 - 4" High volume desilting cones, 100 GPM ea, 15-25 microns cut point.
- 2 - 10" High volume desander cones, 500 GPM ea, 30-40 microns cut point.
- 8" x 8" header pipe with victaulic on each end.
- 0 - 100 PSI liquid filled pressure gauge with diaphragm to prevent plugging.

Series 500 Model B4X-18 DHC10/2 "VGS"

Skidded; 3 screens; processes up to 2000 gal/min.

Gross weight: 4000 lbs.

Option: Add 5" x 6" pump (gross weight with pump: 4600 lbs)

Note: Mesh screens charged out by screen



Mud Masters Group
a division of Horizon Mud Company

Call us to request pricing and additional information.
24 hours: 1 (800) 395-9332 | www.mudmastersgroup.com