

Safety Data Sheet
HFA-266

SECTION I - IDENTIFICATION



ProChem Energy Services, Inc
9396 Hwy 76
Healdton, OK 73438 U.S.
(580) 229-0522
INFOTRAC: (800) 535-5053

Product Number HFA-266
Product Name HFA-266
Chemical Family Amine Based Corrosion Inhibitor
CAS Number Multiple
Date Prepared 1/15/2016
Revision Number
Recommended Use For Industrial Use Only

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Flammable Liquids	Category 3
Corrosive to Metals	Category 1
Acute Toxicity, Oral	Category 3
Skin Corrosion/Irritation	Category 1B
Serious Eye Damage/Eye Irritation	Category 1
Acute Toxicity, Inhalation	Category 3
Specific target organ toxicity, single exposure	Category 1
Hazardous to the aquatic environment, acute hazard	Category 3

DANGER!

GHS LABEL:



Hazard Statements

H226	Flammable liquid and vapor
H290	May be corrosive to metals
H301	Toxic if swallowed
H314	Causes severe burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H370	Causes damage to organs

Safety Data Sheet

HFA-266

H402 Harmful to aquatic life

Precautionary Statements

P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition, sources. No smoking.
P233	Keep container tightly closed.
P234	Keep only in original packaging
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light.../ equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures to prevent static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated are.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
P308+311	IF exposed or concerned: Call POISON CENTER/doctor/physician
P310	Immediately call a POISON CENTER or doctor/physician.
P311	Call a POISON CENTER or a doctor/physician.
P321	Specific treatment (see ... on this label).
P330	Rinse mouth.
P363	Wash contaminated clothing before reuse.
P370+378	In case of fire: Use..... to extinguish.
p390	Absorb spillage to prevent material damage.

Safety Data Sheet

HFA-266

P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.
P405	Store locked up.
P406	Store in a corrosive resistant/... container with a resistant inner liner.
P501	Dispose of contents/container to...

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
Organic Acid	proprietary	0.1-30%	10 ppm	10 ppm
Proprietary Amine Compound	proprietary	0.1-30%	Not Established	Not Established
Methanol	67-56-1	0.1-30%	200 ppm(Skin)	200 ppm(Skin)
Quaternary Pyridine Salt	Proprietary	0.1-30%	Not Established	Not Established

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing Seek immediate medical attention.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, seek immediate medical attention.

Inhalation: Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is affected or stopped. Seek immediate medical attention.

Ingestion: If SWALLOWED: Call a poison control center immediately. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without medical advice. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical advice.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Alcohol resistant foam, carbon dioxide, regular dry chemical, water
Do not use a direct stream of water. Product will float and can be reignited on surface of water.

Special Fire Fighting Procedures Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. Firefighters' protective clothing will provide limited protection.

Safety Data Sheet

HFA-266

Unusual Fire Fighting Hazards: SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, firefighting foam, or Halon.

LARGE FIRES: Water spray, fog or firefighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep out of low areas. Ensure adequate ventilation. Ventilate closed spaces before entering them.

Environmental Precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods for Cleaning Up: Small Spill: Clean up with shovel and broom. Move other containers from spill area. Absorb spill material with an inert absorbent. Use spark proof tools while working in spill area. Contaminated absorbent material may pose same hazards as the spilled product. Dispose of any materials using approved disposal methods. Contact Greenwell Environmental Affairs after area is secure.

Large Spill: Move other containers from spill area. Absorb spill material with an inert absorbent. Approach area from upwind. Dike spill area and do not allow spilled material to reach water systems or drainage systems. Use spark proof tools while working in spill area. Dispose of any materials using approved disposal methods. Contaminated absorbent material may pose same hazards as the spilled product. Contact Greenwell Environmental Affairs after area is secure.

SECTION VII - HANDLING AND STORAGE

Handling and Storage:

- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling. Vent container carefully before opening. Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended. "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS #	OSHA PEL	ACGIH TLV
Organic acid	Proprietary	10 ppm	10 ppm
Proprietary Amine Compound	Proprietary	Not Established	Not Established
Methanol	67-56-1	200 ppm(Skin)	200 ppm(Skin)
Quaternary Pyridine Salt	Proprietary	Not Established	Not Established

Safety Data Sheet
HFA-266

Engineering Controls: Ensure adequate ventilation, especially in confined areas. Eye wash fountain and emergency showers are recommended.

Monitoring: Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure. Use good personal hygiene practices. Avoid repeated and/or prolonged skin exposure. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove contaminated clothing and laundry before reuse. Use care when laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Consider the need to discard contaminated leather shoes and gloves.

Personal Protective Equipment (PPE)

Eye Protection: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

Skin Protection: Gloves constructed of nitrile or neoprene are recommended. Other chemical resistant gloves are acceptable.
If needed to prevent skin contact, chemical protective clothing such as of DuPont TyChem®, Saranex or equivalent recommended based on degree of exposure. The resistance of specific material may vary from product to product as well as with degree of exposure

Respiratory Protection: Use a NIOSH-approved respirator as required to prevent overexposure. In accord with 29 CFR 1910.134, Use either a full-face, atmosphere-supplying respirator or an air-purifying respirator

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear amber liquid
Odor	Slight Alcohol odor
pH@25°C	6-8
Melting/Freezing Point	Not Available
Flashpoint	128°F
Specific Gravity	1.0083 or 447 lbs/gal
Solubility	Water Soluble
Auto-Ignition Temperature	Not Available
Decomposition Temperature	Not Available
VOC Content	Not Available
Odor Threshold	Not Available
Boiling Range	Not Available
Evaporation Point	Not Available
Flammable Limits - Upper	Not Available
Flammable Limits - Lower	Not Available
Vapor Pressure	Not Available
Vapor Density (Air=1)	Not Available
Viscosity	Not Available

Safety Data Sheet
HFA-266

SECTION X - STABILITY AND REACTIVITY

Stability:	Stable, under normal conditions of storage and handling.
Conditions to Avoid:	Flammable in the presence of the following materials or conditions: open flames, sparks, static discharge and heat.
Hazardous Decomposition/Byproducts:	Carbon monoxide, Carbon dioxide Noncombusted Hydrocarbons
Hazardous Polymerization:	Will not occur.
Polymerization Conditions to Avoid:	None
Incompatibilities:	Can react with strong oxidizing agents, peroxides, alkaline products and strong acids. Contact with amines, ammonia, and some metals can create hazards. Avoid contact with Aluminum and Copper. Mildly corrosive to carbon steel.

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure:	Contact and inhalation; ingestion possible.
Inhalation:	Inhalation is not expected unless small particulates or heated to high temperatures. Inhalation of concentrations over 50 ppm can produce headache, lassitude, weariness, dizziness, drowsiness, over excitation. Exposure to very high levels can result in unconsciousness and death. Repeated over-exposure may cause liver and kidney injuries. Components of the product may affect the nervous system. Exposure to light hydrocarbons has been associated in animal studies with effects to the central and peripheral nervous systems, liver, and kidneys. The significance of these animal models to predict similar human response to gasoline is uncertain.
Eye Contact:	Causes severe irritation, experienced as discomfort or pain, excess blinking and tear production, marked excess redness and swelling of the conjunctiva, and chemical burns of the eye
Skin Contact:	Causes severe skin irritation Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.
Ingestion:	Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema. Ingestion of liquid will cause gastrointestinal distress, irritation, possibly nausea, and can be fatal.
Acute Toxicity Value:	Eye or skin contact will result in serious burns and may cause blindness.

Safety Data Sheet
HFA-266

Chronic (Long Term) Effects: See Health Hazards above.

Toxicity:

Component Name	LD50	LC50
Organic Acid	Oral - rat - 3,310 mg/kg; Dermal - rabbit - 1,060 µl/kg;	Inhalation - mouse - 1H/5,620 ppm
Proprietary Amine Compound	Not Established	Not Established
Methanol	Oral - Human - 143 mg/kg; Oral - rat - 1,187 - 2,769 mg/kg;	Inhalation - rat - 4 h - 128.2 mg/l; Inhalation - rat - 6 h - 87.6
Quaternary Pyridine Salt	Not Established	Not Established

Reproductive Effects Not Applicable
Teratogenicity Not Applicable
Mutagenicity Not Applicable
Embryotoxicity Not Applicable
Sensitization to Product Not Applicable
Synergistic Products Not Applicable
Carcinogenicity Not listed as a Carcinogen

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: This chemical is not listed as toxic to aquatic organisms, however, does contain substances dangerous for the environment. Use care to not allow the chemical into any water way. May cause long-term adverse effects in the aquatic environment.

Mobility: Mobile in soil

Degradability: Readily biodegradable

BioAccumulation: This material is not expected to significantly bio accumulate.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Safety Data Sheet

HFA-266

The generation of waste should be avoided and minimized at all times. Empty containers may contain a residue of this product. Processing, use or contamination of the product may change the waste management options. Must not be disposed of together with household garbage. Any unused product should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility.

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: UN2924, Flammable liquid, Corrosive liquid, n.o.s., 3, 8, PGIII
Contains: Ethoxylated Amine
Hazard Class and Label: 3, 8
Identification Number: UN2924
Packaging Group: III
Other Shipping Info: ERG 132

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X		X		

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

Component Name	CAS #	% by wt.
Methanol	67-56-1	0.1-30%

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

Component Name	CAS #	% by wt.	RQ (lbs.)
Organic acid	Proprietary	0.1-30%	5,000
Methanol	67-56-1	0.1-30%	5,000

CALIFORNIA PROPOSITION 65:

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

SECTION XVI - OTHER INFORMATION

HMIS Health: 3

Safety Data Sheet

HFA-266

HMIS Flammability: 3

HMIS Reactivity: 0

Additional: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.